



INNOVATION IS OUR SPECIALTY. SERVICE IS OUR PASSION.
CONCEPT SURFACESTM

POST INSTALLATION CLEANING AND MAINTENANCE OF PORCELAIN FLOOR TILES

The following maintenance recommendations are based on general cases. If these do not fit the needs required, please contact info@conceptsurfaces.com to find a solution!

Recommendations for a new installation – Products are produced by Fila Solutions. Contact info@conceptsurfaces.com to purchase.

Grout Haze Remover (For cement based grouts): DETERDEK - Acidic Cleaner

Coverage: 1,630 sq ft / GAL

Dilution: 1:5 in water

Materials Needed: DETERDEK, Green scrubbing pad, Microfiber Cloth, Floor Scrubbing Machine.

- Distribute the diluted DETERDEK evenly across the porcelain using a long handled brush or similar applicator
- Scrub the surface with a green scrubbing pad
- Remove any remaining residue with a wet vacuum or a clean microfiber cloth.
- Thoroughly rinse the surface with a synthetic mop. Use one bucket to hold clean water and another bucket to strain dirty mop water.

Grout Haze Remover (For epoxy based grouts): EPOXYOFF - Epoxy Grout Haze Remover

Coverage: up to 100 sq ft / QT

Dilution: full strength

Materials Needed: EPOXYOFF, Green scrubbing pad, Microfiber Cloth, Floor Scrubbing Machine.

- Distribute the undiluted EPOXYOFF evenly across the porcelain using a long handled brush or similar applicator
- Let the product sit on the haze for 30 minutes
- Scrub the surface with a green scrubbing pad and a little water
- Remove any remaining residue with a wet vacuum or a clean microfiber cloth.
- Thoroughly rinse the surface with a synthetic mop.

Routine Maintenance Cleaner: CLEANALL – Ph balanced cleaner

Coverage: 61,115 sq ft / GAL

Dilution: 1:200 in water

Materials Needed: CLEANALL, Synthetic Mop, Long Handled Brush, Floor Washing Machine

- Dilute 1:200 (Capful per gallon)
- Distribute the mixture evenly across the tile using either a synthetic mop, long handled brush, or a floor washing machine
- No rinse is required